ProLite E2210HDS-1

The new ProLite E2210HDS is the latest introduction to iiyama's range of Eco-monitors showing a commitment to the environment whilst still offering the latest technology and value for money. The true high definition panel is 1920x1080, 16:9 format and offers fast 2ms response time and 20,000:1 ACR for improved colour in gaming and video applications. It also features the latest triple input configuration of HDMI, DVI and analogue and is Energy Star® qualified.

Panel	TN
Diagonal	22"
Display area h x w	268.1 x 476.6 mm; 10.6" x 18.8"
Response time	2 ms
Contrast	20 000 : 1 ACR
Contrast	1000 : 1 typical
Brightness	250 cd/m² typical
Viewing zone	horizontal/vertical: 170°/160°; right/left: 85°/85°; up/down: 80°/80°
Display colour	16.7 million
Pixel pitch h x v	0.248 x 0.248 mm
Native resolution	Full HD 1080p, 1920 x 1080 (2.1 megapixel)
Horizontal sync	24 - 80 KHz
Vertical sync	55 - 75 Hz
Analog input connector	D-Sub
Digital input connector	DVI-D, HDMI
HDCP	yes
Synchronization	Separate Sync
Plug & Play	VESA DDC2B™
Speakers	2 x 2 W (Stereo)
Included accessories	power cable, D-Sub cable, DVI-D cable, audio cable,stand, quick start guide
Apple - Mac	All iiyama monitors are compatible with Apple-Macintosh computers.
Controls	Via OSD in 9 languages (EN, DE, FR, ES, IT, PT, Chinese, RU, JP) and 5 front controls (Power, Menu/ Select, +/ Volume, -/ ECO, Auto)
User controls	luminance (contrast, brightness, ECO, picture mode, ACR), image setup (clock, phase, H. position, V. position, aspect), colour adjust (colour temperature, gamma), OSD setup (H. position, V. position , time out, language), others (reset, signal select, HDMI audio, OD, information), volume, auto adjust
Ergonomics	CE, TÜV-Bauart, PSE
Power supply	AC 100 - 240 V, 50 / 60 Hz
Power Supply Unit	internal
Power usage	24 W typical; max. 1 W in Power management mode
Power management	VESA DPMS, ENERGY STAR®
Anti-theft-device	Kensington-lock™ prepared
VESA mounting	100 mm
Tilt angle	20° up; 5° down
Dimensions w x h x d	505.5 x 366 x 180 mm
Weight	3.5 kg
Aspect ratio	16 : 9

All trademarks and registered trademarks acknowledged. E & O E. Specification subject to change without notice. All LCD's comply with ISO-13406-2 in connection with pixel defects.